

PREPARING iPad

- iPads need to be unwrapped and removed from packaging
- iPads need to be updated to iPadOS 13.4 or later
This may require being connected to power. Please have charging cables available.
- If asset tags are used on iPads, install tags in a location visible through the Rugged Combo 3 Touch window prior to installing iPad into Logitech® Rugged Combo 3 Touch.

RUGGED COMBO 3 TOUCH

ASSEMBLY 30 seconds or less

- 1 Review any documentation that comes with the packaging
- 2 Place your iPad inside the case
- 3 Ensure the camera and camera opening are lined up
- 4 Press down on all four corners to secure it
- 5 Pull out the adjustable kickstand and fold the keyboard downward
- 6 If using, place your Logitech Crayon or Apple Pencil inside the magnetic latch

DISASSEMBLY 5 seconds

- 1 One at a time, press each of the four corners of the case
- 2 Take iPad out of the case

STORAGE AND TRANSPORTATION

When transporting or storing Rugged Combo 3 Touch iPad units, stacking vertically can minimize weight and pressure on units, which will reduce the risk of damage. If horizontal stacking is needed, do not stack more than 4 units on top of each other.

CLEANING

Spray cleaning liquid onto a cloth and wipe, do not spray directly onto the case or trackpad. Microfiber cloths can be used effectively with just water, however non-toxic or chemical cleansers that do not contain bleach can be used. Ensure the case is completely dry before storing.

Learn more at
www.logitech.com/education/cleaning-solutions.html